



JEMChair®



**Model JEM00, JEM10
750 lb. capacity**

Dimensions

Seat Width	19½"	Back Width	19½"
Outside Width		Seat Depth	18½"
armless	21½"	Seat Back Height	16"
with arms	25"	Outside Depth	24"
Seat Height from floor	17½"		

COM Yardage

Seat/Back Yardage 1¼ yards (back only ¾ yard, seat only ½ yard)

Steel Frame

¾" tubular, welded, 14 gauge steel, one piece construction. Multiple stretcher bars located under the seat for added strength. Back attachment flanges. Powder coated black or gray color.

Foam

CAL117-2013. High density 2.5 lb. cut seat foam providing extreme comfort and longevity. 1" extra seat foam offered as option. Back foam 1.8 lbs. density. Also available with optional CAL133.

Seat

1½" thick foam, ⅝" thick 7 plywood substrate platform.

Back

½" thick 7 plywood front panel substrate platform with ½" foam. Compound double curved angles provide extreme comfort via a nesting or cradle effect. ⅝" 3 plywood rear panel with ½" foam. Back attachment hardware is "sandwiched" between the front and back panel concealing all mounting frame hardware. Provides a clean and attractive back appearance.

Back Panel

Standard upholstered or black ballistic nylon.

Back Attachment Method

Locking "Z" clip back panel attachment. Sandwiched between the front and back panel and NOT exposed providing clean back appearance.

Arms

Durable nylon and angled outward to provide additional seat width. Available in black or gray color.

Glides

Standard 1½" high black nylon glides. On site interchangeable with casters. Casters available for carpet or hard floor surface. Glides are non-marring.

Casters

Interchangeable on site with 1⅝" dual wheel high black nylon glides. Available for carpet or hard floor surfaces.

Wall Saving Leg

Standard with every chair adding stability.

Weight Capacity

Published warranty of 750 lbs. Static load test to 3,944 lbs.

Stacking

4 high on floor without a dolly.

Assembly

One piece construction. Ships fully assembled.

Warranty

Lifetime on components. 5 years on fabric and foam.